



# Keeping you Moving

## T-800 CROSS-PLY PORT TIRES



E3



E4

**T-800 Port Tires designed for container handling applications.**

**Designed for use on Reach Stackers, Straddle Carriers, Gantry Cranes, Top Lift Container Handlers, and Heavy Range Forklifts.**

- ▶ Suitable for high use and heavy load applications
- ▶ Standard industry tread patterns provide excellent wear on abrasive surfaces
- ▶ Cross-Ply build offers excellent stability

### T-800 RANGE

Tire Size	PR	LI/SI	Rim	Pattern Type	Tread Depth [mm]	Width [mm]	Overall Diameter [mm]	Inflation Pressure [bar]	Load Capacity @ 10 km/h [kg]	Load Capacity @ 25 km/h [kg]	Load Capacity @ 40 km/h [kg]	Load Capacity @ 50 km/h [kg]
16.00-25	32	177 B	11.25-25/2.0	E3	29	432	1493	6.5	-	7900	7500	7300
18.00-25	40	206 A2	13.00-25/2.5	E4	54	500	1675	9.5	17000	13600	-	-
18.00-33	40	212 A2	13.00-33/2.5	E4	71	500	1875	9.5	20000	16000	-	-

WWW.TRELLEBORG.COM/WHEELSYSTEMS

